



Greenflow Series

Maintenance Guidelines

Maintenance Guidelines


Lasting beauty of your floor can be achieved through proper care and regular maintenance. Failure to follow these guidelines can void your warranty. Visit www.opusfloors.ca to get more maintenance information.



■ How to maintain a cork floor as new for a long life?

For day to day cleaning, Green Flow cork floors should be cleaned with only a mist or spray type cleaner suitable for hardwood or cork floors. Never use pre-treated dusters or wet-jet type cleaners or hydrogen peroxide as these can damage the finish. Any damage caused by excessive moisture or unsuitable cleaners will not be covered under the warranty. Never wet mop a cork floor.

- If work will take place in the room where the floor is installed, protect with craft paper, plywood or hardboard.
- Avoid excess moisture on the floor. When mopping use a damp, not soaking wet mop. Liquids can make the seams swell or ruin your subfloor.
- Place quality walk-off mats at all entrances to collect any dirt, moisture or other abrasive substances that can harm your floor.
- Cork, as a natural material, may tend to fade when exposed to sunlight. Cork and wood, are natural products, color change may be expected when exposed to light over a period of time. Cork will tend to fade while wood tends to mellow or darken. It is important to move area rugs and furnishings to allow for even color change.
- Use blinds, curtains or other sun screening system to keep direct sunlight off the cork floor on sunny days when possible. Moving furniture and area rugs from time to time can help fading to occur more evenly.
- Using felt pads floor protectors on chairs and furniture legs are always recommended to reduce scratching or gouging.
- Keep pets claws/nails trimmed to protect floor from pet related damage, they can scratch and damage the cork.
- Do not drag furniture across the floor. If you are moving appliances or heavy furniture never slide them across the floor.
- Office roller chairs must comply with DIN 68131 (Type W1). Use protective office mats under the rolling chairs.



- Place area rugs or mats in front of the kitchen appliances and sink to protect your cork floor from a lot of traffic, water spillages, dropping food, grease, and everything else that can cause premature wear of your kitchen floor.
- Never use cleaning products with abrasive ingredients or solvent based, e.g. acetone.
- Never use latex or rubber backed mats as they can permanently stain the floor.
- Never use wire brushes.
- When using intensive room heating, the indoor air humidity may drop so low that the floor is prone to dry out. As cork is a natural material, this may cause shrinkage of the tiles that will result in minor gaps in the flooring joints. Use a room humidifier to prevent this.
- Ideal and healthy room conditions are 35 - 65 % R.H. at 20°C (68°F).
- Green Flow cork flooring is remarkably resilient and will recover from most indentations and pressure marks over time. In the event the floor becomes gouged or cut, fill sticks are available at most hardware stores and can be used to fill these spots. Significant damage may require replacement of individual tile.

■ How to properly clean and maintain a cork floor?

Our Cork floors are very easy to maintain and you only need one of the listed products and a vacuum cleaner.

For daily/weekly maintenance, you may use a broom handle with a cloth on the end. The removable cloth has a substance with anti-static characteristics, which will clean all the dust and prevent its settling on the floor. Before wiping the floor with a damp mop - vacuum, broom or sweep the cork floor to remove all loose dirt. This avoids dirt to penetrate on the embossing and joints of the floor.

Use a damp but not soaking wet mop and water to clean general spills. When deep cleaning the floor, use a damp mop with recommend floor cleaners formulated for cork floors. You



should avoid excessive moisture, so never flood the floor when mopping.

Oil Soaps and Ammonia Cleaners – There are many products oil soap based or silicone, wax, or ammonia based cleaning products that will damage and dull the finish of your cork floors. Always avoid the use of harsh abrasives and oil or ammonia-based cleaning products.

Remember to only use cleaning products approved by CORKSRIBAS/OPUSFLOORS.

■ **Can I walk over the cork floor and clean it immediately after it's installed?**

In the case of a glue-down installation method, you should wait 24-36 hours after installation of the floor to allow the flooring adhesive to dry completely before walk on or mop your new cork flooring. This helps to avoid shifting the flooring before it is set in place.

As for a floating or glue-less installation, it can be walked on and mopped only with a damp mop, immediately after installation.

■ **How to remove a dried adhesive from the surface of my cork flooring after installation?**

As soon as the adhesive has dried, you can remove any excess by wiping with a soft cloth and mineral spirits.

■ **How to move heavy objects over my flooring?**

The ideal scenario should be lifting and place your object into the location you want it. If you cannot do this, lay down a hard surface such as plywood and create a path to the location where your object will be placed. Please make sure the plywood is thick and large enough to disperse the weight of the object. A moving blanket should also be placed under the plywood to prevent any scratching.

■ **Can I re-finish my cork floor?**

Yes, varnishing is as simple and all our cork products are low-VOC, low-odor and water-based.



In this situation, we recommend a range of varnishes, which will give typical industry results. For the correct use, follow the instructions on the packaging labels of each product, as well as the information from technical data sheets.

Please note that in the Glue-down floors, you should wait 24-36 hours after installation of the floor, to allow the flooring adhesive to dry completely.

■ Refurbishment

The renovation of an old and used floor cannot be recommended if we don't know its history, especially the kind of maintenance products which have been used.

If we know all about maintenance products and we can guarantee that all maintenances products are removed completely, we can apply one coat of the recommended varnishes.

Residues of maintenance products will cause lack of adhesion and it is recommendable to make an adherence test between the old and new coat, on a small area before the final varnishing.

The floor should not be cleaned with water or detergent for about two weeks, after applying the varnish. After this period use CORKSRIBAS/OPUSFLOORS recommended maintenance products.

Once again, for the correct use follow the instructions on the packaging labels of each product, as well as the information from technical data sheets.

Product	Brand	Green Flow Accessories
Cleaner	Bona	Bona Hardwood Floor Cleaner
	Bona	Ultracoat Clean WPM
Stripper	Bona	Bona Remover
	Mapei	Ultracoat Remover
Recoating	Bona	Diamond Abrasive and Traffic Urethane
	Mapei	Ultracoat HT 2K (use with Diamond Abrasive)
Adhesive	Mapei	Ultrabond Eco 983