



18/4 x 190 x 1900mm (approx. 3/4" x W7 1/2" x 6'3") **Mozart Oak**



18/4 x 150 x Random Length (approx. 3/4" x W6" x Random Length) **Mayfield Walnut II**



12/3 x 190 x Random Length (approx. 3/4" x W7 1/2" x Random Length) **Angel Oak**

Classical Series



Shawnee Series



Creek Series



Good	Better	Best
Creek Series	Shawnee Series	Classical Series
1/2" x 6 1/2" - 7 1/2" Random Length	3/4" x 6" - 7 1/2" Random Length	3/4" x 7 1/2" x 6'2" - 6'3" Fixed Length Proportion: Oak 85%/Maple 33%
6 ply	9 ply	9 ply
Eucalyptus & Poplar Core	Eucalyptus & Poplar Core	Eucalyptus & Poplar Core
UV Oil/UV Urethane	UV Oil/UV Urethane	Natural Oil*/UV Urethane
2-3mm wearlayer	4mm wearlayer	4mm wearlayer
Nail/Float/Glue down	Nail/Float/Glue down	Nail/Float/Glue down
Radiant Heat Approved	Radiant Heat Approved	Radiant Heat Approved
Meets CARB2 Standard	Meets CARB2 Standard	Meets CARB2 Standard
Designed & Manufactured Eco Friendly	Designed & Manufactured Eco Friendly	Designed & Manufactured Eco Friendly

Opus **Classical Series** engineered hardwood floors are finished with either UV Urethane or Osmo Polyx®-Oil. This NATURAL product uses the newest most advanced NATURAL processes. The finishes are derived from natural plant, vegetable oils and waxes. These ***NATURAL Oils** are microporous and molecularly bond with the wood, meaning no cracking, flaking or peeling. Open pores allow for absorption of VOCs for healthier air. When adequate amounts of Osmo Polyx®-Oil are present, the floor will be resistant to water, dirt, beer, wine, cola and saliva. Using regular cleaning and maintenance with oil soap (Osmo Wash and Care) will postpone the need for eventual application of maintenance oil to rejuvenate and maintain floor protection.

Opus **Shawnee Series** and **Creek Series** engineered hardwood floors are finished with either UV Urethane or WOCA UV Oil. ****UV Oil** finish has similar properties to Natural oil, however it is sealed by UV light which requires less maintenance than Natural oil finishes. Eventually, UV Oil will require an application of maintenance oil similar to Natural Oil products. Both Natural Oil and UV Oil finishes require the correct maintenance to ensure optimum levels of protection. UV Oil (WOCA) and Natural Oil (Osmo) finishes must be maintained with recommended maintenance products.

The advantages of UV Oil/Natural Oil finishes vs. UV Urethane finishes are that they can be spot-repaired and/or restored/renewed, and in most cases with no sanding required at lower cost and disruption. UV Urethane finishes are able to resist absorption of stains and spills longer than either UV or Natural Oil finishes.

SUPERIOR WEARLAYER and MULTIPLY CONSTRUCTION for LONGER LIFE & GREATER STABILITY



Products listed can and do change, to confirm current products, to view larger images and to get more information, please visit www.opusfloors.ca

