

## SILENT CORK UNDERLAY



Name Cork Underlay 1/4"thick x 24"W x 36"L (6 x 610 x 914mm) 1/8"thick x 24"W x 36"L (3 x 610 x 914mm)	
Size (6 x 610 x 914mm) 1/8"thick x 24"W x 36"L (3 x 610 x 914mm)	
1/8"thick x 24"W x 36"L (3 x 610 x 914mm)	_
(3 x 610 x 914mm)	
1/4"(6mm):	
50sheets/ctn; 300sqft/ctn	
Qty 1/8" (3mm):	
100sheets/ctn;600sqft/ctr	i
Weight 120-180kg/m3	
Strength ≥ 200 kPa;	
Feature Compression: 40-60%	
Recovery: ≥ 75%	



- Easy to install
- Improve acoustic and thermal comfort
- Maximize the service life of joining system
- Avoid the diffusion of vapor

- Reduce subfloor imperfections
- Increase floor durability
- Prevent cracks and marks on the floor
- Chemical inert, moisture resistance and biodegradable.



WALKING COMFORT



RESILIENCE & COMPRESSIBILITY



RESISTANCE & FLEXIBILITY



NCE & THERMAL INSULATOR



ACOUSTICAL INSULATOR



HYPOALLERGENIC



Silent cork underlays are made out of natural cork – an excellent raw material suitable to be installed under almost any floor covering with significant improvement at thermic and acoustic levels. When compared to synthetic materials, cork becomes the right choice when looking for a solution that guarantees a viable performance but also the welfare of future generations. Acoustic silent cork underlay provides more comfort, protection and longevity to the final floor.